



### CNC Lathe

Type	Distance between the centers	Ø Swing over bed	Ø Swing over cross slide
Doosan Puma 5100LY *	2 meter	Ø 850 mm	Ø 550 mm

\* With 12 power tools

### Teach-Inn Lathe

Type	Distance between the centers	Ø Swing over bed	Ø Swing over cross slide
Emcomat E-360	2 meter	Ø 810 mm	Ø 480 mm
Emcomat E-300	2 meter	Ø 570 mm	Ø 340 mm
Emcomat E-300	1,5 meter	Ø 570 mm	Ø 340 mm
Emcomat E-300	1,5 meter	Ø 570 mm	Ø 340 mm

On all our lathes we can run a maximum stroke of 8 meters

### Conventional Lathes

Type	Distance between the centers	Ø Swing over bed	Ø Swing over cross slide
Potisje PA35	4 meter	Ø 700 mm	Ø 500 mm
Potisje PA35	4 meter	Ø 700 mm	Ø 500 mm
Potisje PA30	3 meter	Ø 610 mm	Ø 400 mm
Potisje PA30	2 meter	Ø 610 mm	Ø 500 mm

### Milling machine

Type	Stroke X-axis	Stroke Y-axis	stroke Z-axis
Cinch-Mill 30 *	1500 mm	550 mm	500 mm
Maquinaria CMEFU.2cm	1100 mm	300 mm	600 mm

\* With 24 tools

### Honing machine

Type	Stroke	Hoon range
Sunnen	1.850 mm	40 – 140 mm



## HYDRAULIC CYLINDERS

ABS Group B.V.  
De Zwaaiikom 3  
9641 KV VEENDAM  
Nederland

t: +31 (0) 598-622544  
f: +31 (0) 598-620875  
e: [info@abshydro.com](mailto:info@abshydro.com)  
i: [www.abshydro.com](http://www.abshydro.com)

### Drills

Type	drill Ø	
Serrmac TCS40	40 mm	Digital with stitch circle program
Bimax 45	40 mm	With cross support
Gromatic 40a	40 mm	With cross support

### Welding

Type	Type	Kind
Fronius	VR4000	Mig/Mach
Fronius	VR4000	Mig/Mach
Fronius	VR4000	Mig/Mach
Fronius	Transtich 3000	TIG

### Las Manipulator

Type	Capacity	Bore
Manipulator	2500 kg	Ø 1250 mm
Manipulator	800 kg	Ø 800 mm
Manipulator	800 kg	Ø 800 mm
Manipulator	800 kg	Ø 800 mm
Manipulator	600 kg	Ø1000 mm
Manipulator	250 kg	Ø 400 mm

### Sawing machine

Type	
HB5300	Ø 300 mm